



























تصویر محصول	شرح ویژگی	قیمت	پارت نامبر	ردیف
	<p>1/2.8" progressive scan CMOS 1920 × 1080@30fps 2.8 mm/4 mm/6 mm fixed lens H.265+, H.265, H.264+, H.264 Dual stream Digital WDR (Wide Dynamic Range) 3D DNR (Digital Noise Reduction) Up to 30 m IR range PoE (Power over Ethernet) IP67</p>	ریال ۲۰,۱۴۰,۰۰۰	DS-2CD1023G0-I	۱
	<p>1/3" progressive scan CMOS 2560 × 1440@20fps 2.8 mm/4 mm/6 mm fixed lens H.265+, H.265, H.264+, H.264 Dual stream 120 dB WDR (Wide Dynamic Range) 3D DNR (Digital Noise Reduction) Up to 30 m IR range IP67</p>	ریال ۲۷,۵۶۰,۰۰۰	DS-2CD1043G0-I	۲
	<p>High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Robust structure design with full metal materials.</p>	ریال ۳۱,۴۵۰,۰۰۰	DS-2CD2023G0-I	۳
	<p>High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Robust structure design with full metal materials.</p>	ریال ۳۵,۹۲۰,۰۰۰	DS-2CD2043G0-I	۴





تصوير محصول	شرح ويژگي	قيمت	پارت نامبر	رديف
	<p>High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Robust structure design with full metal materials.</p>	<p>ريال ٤٠,٠٧٠,٠٠٠</p>	<p>DS-2CD2T43G0-I5</p>	<p>٥</p>
	<p>High quality imaging with 6 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Robust structure design with full metal materials.</p>	<p>ريال ٤٨,٧٦٠,٠٠٠</p>	<p>DS-2CD2T63G0-I8</p>	<p>٦</p>
	<p>High quality imaging with 8 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Robust structure design with full metal materials.</p>	<p>ريال ٥٧,٩٥٠,٠٠٠</p>	<p>DS-2CD2T83G0-I8</p>	<p>٧</p>
	<p>1920 x 1080@30fps 2.8 mm to 12 mm motorize varifocal lens H.265+, H.265, H.264+, H.264 BLC/3D DNR/ROI Up to 30 m IR range IP67 Digital WDR Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>	<p>ريال ٤٥,٩٤٠,٠٠٠</p>	<p>DS-2CD1623G0-IZ</p>	<p>٨</p>




تصویر محصول	شرح ویژگی	قیمت	پارت نامبر	ردیف
	2560 × 1440@20fps 2.8 mm to 12 mm varifocal lens H.265+, H.265, H.264+, H.264 BLC/3D DNR/ROI Up to 30 m IR range IP67 120 dB WDR Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	ریال ۴۹,۴۷۰,۰۰۰	DS-2CD1643G0-I	۹
	Up to 2 Megapixel (1920 × 1080) Resolution Full HD1080p Real-Time Video 2.8 mm to 12 mm varifocal lens IR LEDs Up to 30 Meters Range DWDR, 3D DNR, and BLC IP66 Supports On-Board Storage Up to 128 GB	ریال ۴۴,۶۵۰,۰۰۰	DS-2CD2620F-I	۱۰
	Up to 3 Megapixel (2048 x 1536) Resolution Full HD1080p Real-Time Video 2.8 mm to 12 mm varifocal lens IR LEDs Up to 30 Meters Range DWDR, 3D DNR, and BLC IP66 Supports On-Board Storage Up to 128 GB	ریال ۴۸,۰۶۰,۰۰۰	DS-2CD2632F-I	۱۱
	High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology audio and alarm interface available Water and dust resistant (IP67) Motorized vari-focal lens for easy installation and monitoring Robust structure design with full metal materials	ریال ۷۴,۲۰۰,۰۰۰	DS-2CD2643G0-IZS	۱۲




تصویر محصول	شرح ویژگی	قیمت	پارت نامبر	ردیف
	<p>1/2.8" progressive scan CMOS 3D DNR 1920 × 1080@30fps Up to 30 m IR range 2.8 mm/4 mm fixed lens IP67, IK10</p>	<p>ریال ۲۱,۵۶۰,۰۰۰</p>	<p>DS-2CD1123G0-I</p>	<p>۱۳</p>
	<p>1/3" progressive scan CMOS 3D DNR (Digital Noise Reduction) 2560 × 1440@20fps Up to 30 m IR range 2.8 mm/4 mm fixed lens H.265+, H.265, H.264+, H.264 IP67, IK10 Triple stream 120 dB WDR (Wide Dynamic Range)</p>	<p>ریال ۲۸,۹۸۰,۰۰۰</p>	<p>DS-2CD1143G0-I</p>	<p>۱۴</p>
	<p>High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology audio and alarm interface available Water and dust resistant (IP67) and vandal proof (IK10) Robust structure design with full metal materials</p>	<p>ریال ۲۳,۹۲۰,۰۰۰</p>	<p>DS-2CD2123G0-IS</p>	<p>۱۵</p>
	<p>High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology audio and alarm interface available Water and dust resistant (IP67) and vandal proof (IK10) Robust structure design with full metal materials</p>	<p>ریال ۳۶,۷۵۰,۰۰۰</p>	<p>DS-2CD2143G0-IS</p>	<p>۱۶</p>




تصویر محصول	شرح ویژگی	قیمت	پارت نامبر	ردیف
	<p>High quality imaging with 6 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology audio and alarm interface available Water and dust resistant (IP67) and vandal proof (IK10) Robust structure design with full metal materials</p>	<p>ریال ۴۳,۸۲۰,۰۰۰</p>	<p>DS-2CD2163G0-IS</p>	<p>۱۷</p>
	<p>High quality imaging with 8 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology audio and alarm interface available Water and dust resistant (IP67) and vandal proof (IK10) Robust structure design with full metal materials</p>	<p>ریال ۵۱,۵۹۰,۰۰۰</p>	<p>DS-2CD2183G0-IS</p>	<p>۱۸</p>
	<p>1/2.8" progressive scan CMOS 1920 x 1080@30fps H.265+, H.265, H.264+, H.264 Dual stream Digital WDR (Wide Dynamic Range) 3D DNR (Digital Noise Reduction) Up to 30 m IR range IP67, IK10</p>	<p>CALL</p>	<p>DS-2CD1723G0-I</p>	<p>۱۹</p>
	<p>1/3" progressive scan CMOS 2560 x 1440@20fps H.265+, H.265, H.264+, H.264 Dual stream 120 dB WDR (Wide Dynamic Range) 3D DNR (Digital Noise Reduction) Up to 30 m IR range IP67</p>	<p>ریال ۴۴,۵۲۰,۰۰۰</p>	<p>DS-2CD1743G0-I</p>	<p>۲۰</p>




تصویر محصول	شرح ویژگی	قیمت	پارت نامبر	ردیف
	<p>1/3" Progressive Scan CMOS 2688 x1520@30fps 2.8 to 12 mm varifocal lens H.265+, H.265, H.264+, H.264 Three streams 120dB WDR BLC/3D DNR/ROI/HLC IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>	<p>CALL</p>	<p>DS-2CD2743G0-IZS</p>	<p>۲۱</p>
	<p>High quality imaging with 5 MP resolution 180° fisheye view Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology.</p>	<p>ریال ۸۷,۱۱۰,۰۰۰</p>	<p>DS-2CD2955FWD-IS</p>	<p>۲۲</p>
	<p>High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Provides real-time security via built-in two-way audio Detects human body through passive infrared is sensitive to body temperature (PIR) Wi-Fi connection</p>	<p>ریال ۲۸,۲۷۰,۰۰۰</p>	<p>DS-2CD2423G0-IW</p>	<p>۲۳</p>
	<p>High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Provides real-time security via built-in two-way audio Detects human body through passive infrared is sensitive to body temperature (PIR) Wi-Fi connection</p>	<p>ریال ۳۴,۹۸۰,۰۰۰</p>	<p>DS-2CD2443G0-IW</p>	<p>۲۴</p>





تصویر محصول	شرح ویژگی	قیمت	پارت نامبر	ردیف
	<p>Up to 1.0 megapixel resolution Support motorized Pan & Tilt Digital WDR 3D DNR IR range approx. 10 meters Support Wi-Fi, support WPS configuration with one touch W) Two way audio Support 128 G on board storage</p>	<p>ریال ۲۴,۸۷۰,۰۰۰</p>	<p>DS-2CD2Q10FD-IW</p>	<p>۲۵</p>
	<p>High quality imaging with 2 MP resolution Efficient H.264 compression technology Clear imaging even with strong back lighting due to DWDR technology Up to 128 GB SD card slot for storage Provides real-time security via two-way audio Wi-Fi connection and easy installation Hik-Connect cloud service and app for remote management and viewing of devices</p>	<p>ریال ۱۷,۳۰۰,۰۰۰</p>	<p>DS-2CV2U21FD-IW</p>	<p>۲۶</p>
	<p>1/2.8" progressive scan CMOS Up to 1920 x 1080@60fps resolution 32x optical zoom, 16x digital zoom WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus Up to 150 m IR distance 24 VAC & Hi-PoE Support H.265+/H.265 video compression</p>	<p>ریال ۱۲۴,۰۱۰,۰۰۰</p>	<p>DS-2DE4225IW-DE</p>	<p>۲۷</p>
	<p>3 lenses in one camera cover up to 360° field of view, ensuring zero-blind zone monitoring Panoramic camera linked to a PTZ: capturing 360° images with the panoramic camera, as well as close-up images with the PTZ camera Built-in IR light: IR range of 15 meters provides good visibility in low or even zero-light environments H.265+/H.265/H.264+/H.264 encoding: efficient compression technology saves storage space and reduces bandwidth requirements</p>	<p>call</p>	<p>DS-2PT3326IZ-DE3</p>	<p>۲۸</p>



تصویر محصول	شرح ویژگی	قیمت	پارت نامبر	ردیف
	<p>Up to 4 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 video formats Up to 6 MP high-definition live view, storage and playback Up to 40 Mbps high incoming bandwidth ensures IP cameras can be connected Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording Compatible with third-party network cameras Plug & Play with 4 Power-over-Ethernet (PoE) interfaces Metal case for professional industry applications.</p>	<p>ریال ۲۷,۲۹۰,۰۰۰</p>	<p>DS-7104NI-Q1/4P/M</p>	<p>۲۹</p>
	<p>Up to 4 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 video formats Up to 6 MP high-definition live view, storage and playback Up to 40 Mbps high incoming bandwidth ensures IP cameras can be connected Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording Compatible with third-party network cameras Metal case for professional industry applications.</p>	<p>ریال ۱۶,۵۲۰,۰۰۰</p>	<p>DS-7104NI-Q1/M</p>	<p>۳۰</p>
	<p>Up to 8 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 video formats Up to 6 MP high-definition live view, storage and playback Up to 4-ch @ 1080p decoding capacity Up to 60 Mbps high incoming bandwidth ensures IP cameras can be connected 1 HDD for continuous video recording Compatible with third-party network cameras Plug & Play with 8 Power-over-Ethernet (PoE) interfaces Metal case for professional industry applications.</p>	<p>ریال ۳۹,۶۸۰,۰۰۰</p>	<p>DS-7108NI-Q1/8P/M</p>	<p>۳۱</p>

تصویر محصول	شرح ویژگی	قیمت	پارت نامبر	ردیف
	<p>Up to 8 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 video formats Up to 6 MP high-definition live view, storage and playback Up to 4-ch @ 1080p decoding capacity Up to 60 Mbps high incoming bandwidth ensures IP cameras can be connected 1 HDD for continuous video recording Compatible with third-party network cameras Metal case for professional industry applications.</p>	<p>ریال ۲۰,۷۷۰,۰۰۰</p>	<p>DS-7108NI-Q1/M</p>	<p>۳۲</p>
	<p>Third-party network cameras supported Up to 8 Megapixels resolution recording Support 1-ch HDMI, 1-ch VGA, HMDI at up to 4K(3840x2160) resolution 1 self-adaptive 10/100/1000 Mbps network interface Connectable to smart IP cameras from Hikvision and the recording, playing back, and backing up of VCA alarms can be realized Support various VCA detection alarm and VCA search Support H.265+/H.265/H.264+/H.264/MPEG4 video formats</p>	<p>ریال ۳۱,۶۰۰,۰۰۰</p>	<p>DS-7608NI-K1</p>	<p>۳۳</p>
	<p>Third-party network cameras supported Supports live view, storage, and playback of the connected camera at up to 8 MP resolution Connectable to smart IP cameras from Hikvision and the recording, playing back, and backing up of VCA alarms can be realized VCA detection alarm is supported Instant playback for assigned channel during multi-channel display mode</p>	<p>ریال ۳۰,۷۳۰,۰۰۰</p>	<p>DS-7608NI-Q1</p>	<p>۳۴</p>

تصویر محصول	شرح ویژگی	قیمت	پارت نامبر	ردیف
	<p>Up to 16 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 video formats Up to 4K high-definition live view, storage and playback Up to 4-ch @ 1080p decoding capacity Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected 1 HDMI and 1 VGA interfaces: both interfaces support independent video output Compatible with third-party network cameras</p>	<p>ریال ۳۷,۰۷۰,۰۰۰</p>	<p>DS-7616NI-Q1</p>	<p>۳۵</p>
	<p>Up to 16 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 video formats Up to 4K high-definition live view, storage and playback Up to 4-ch @ 1080p decoding capacity Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected 1 HDMI and 1 VGA interfaces: both interfaces support independent video output Compatible with third-party network cameras</p>	<p>ریال ۳۸,۷۸۰,۰۰۰</p>	<p>DS-7616NI-Q2</p>	<p>۳۶</p>
	<p>Up to 16 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 video formats Up to 4K high-definition live view, storage and playback Up to 4-ch @ 1080p decoding capacity Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected 1 HDMI and 1 VGA interfaces: both interfaces support independent video output 2 HDDs for continuous video recording Compatible with third-party network cameras Plug & Play with 16 Power-over-Ethernet (PoE) interfaces</p>	<p>ریال ۷۹,۰۰۰,۰۰۰</p>	<p>DS-7616NI-Q2/16P</p>	<p>۳۷</p>

تصویر محصول	شرح ویژگی	قیمت	پارت نامبر	ردیف
	<p>Up to 16 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 video formats Up to 4K high-definition live view, storage and playback Up to 4-ch @ 1080p decoding capacity Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected 1 HDMI and 1 VGA interfaces: both interfaces support independent video output 4 HDDs for continuous video recording Compatible with third-party network cameras</p>	<p>ریال ۸۲,۹۵۰,۰۰۰</p>	<p>DS-7716NI-Q4</p>	<p>۳۸</p>
	<p>Third-party network cameras supported Up to 8 Megapixels resolution recording Support 1-ch HDMI, 1-ch VGA, HMDI at up to 4K(3840x2160) resolution 32-ch network cameras can be connected with 256M incoming bandwidth Up to 4 SATA interfaces Support dual-os to ensure high reliability of system running Support various VCA detection alarm and VCA search Support H.265/H.264/MPEG4 video formats</p>	<p>ریال ۱۲۲,۴۱۰,۰۰۰</p>	<p>DS-7732NI-K4</p>	<p>۳۹</p>
	<p>Up to 32 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 video formats Up to 4K high-definition live view, storage and playback Up to 4-ch @ 1080p decoding capacity Up to 256 Mbps high incoming bandwidth ensures IP cameras can be connected 1 HDMI and 1 VGA interfaces: both interfaces support independent video output 4 HDDs for continuous video recording Compatible with third-party network cameras</p>	<p>ریال ۱۰۲,۳۴۰,۰۰۰</p>	<p>DS-7732NI-Q4</p>	<p>۴۰</p>

تصویر محصول	شرح ویژگی	قیمت	پارت نامبر	ردیف
	<p>H.265+/H.265/H.264/H.264+ video formats Connectable to the third-party network cameras Recording at up to 8 MP resolution HDMI Video output at up to 4K (3840 × 2160) resolution 4 SATA interfaces connectable for recording and backup 16 independent PoE network interfaces are provided playing back, and backing up of VCA alarms can be realized Instant playback for assigned channel during multi-channel display mode Smart search for the selected area in the video; and smart playback to improve the playback efficiency Hik-Connect for easy network management</p>	<p>ریال ۱۴۸,۳۰۰,۰۰۰</p>	<p>DS-7732NI-Q4/16P</p>	<p>۴۱</p>
	<p>Intelligent PoE Management. When the power supply exceeds the limit, PoE ports intelligently manage the power supply, which extends the switch lifetime. Up to 300 m Long Range PoE Transmission. The distance between IPCs and switch can reach maximum 300 meters. 4/8-Core Adaptive Power Supply with Less Power Loss. 8-core power supply reduces the power loss on cables. 6KV Surge Protection to Improve Reliability in Harsh Environment. The built-in surge protection device protects the switch from the sudden lightning surge in harsh environment. Design for Video Transmission. VIP port ensures important data transmission when network congestion occurs.</p>	<p>ریال ۳۰,۲۰۰,۰۰۰</p>	<p>DS-3E0109P-E</p>	<p>۴۲</p>
	<p>Wall Mount Aluminum alloy Hikvision White</p>	<p>ریال ۵,۷۰۰,۰۰۰</p>	<p>DS-1602ZJ</p>	<p>۴۳</p>
	<p>Pendent Mount Aluminum Alloy Hikvision White</p>	<p>ریال ۶,۲۴۰,۰۰۰</p>	<p>DS-1661ZJ</p>	<p>۴۴</p>

ردیف	پارت نامبر	قیمت	شرح ویژگی	تصویر محصول
۴۵	DS-1662ZJ	ریال ۷,۱۶۰,۰۰۰	Pendent Mount (50cm) Aluminum Alloy Hikvision White	
۴۶	DS-1681ZJ	ریال ۲,۰۸۰,۰۰۰	Colour: White Size : 176.8*194*419.5mm Weight:1 kg Material: Aluminium Alloy	

در صورت نیاز به دریافت مشاوره در خصوص هر یک از محصولات فوق میتوانید با شماره تلفن ۶۷۹۵۸ - ۰۲۱ تماس حاصل فرمایید.
شما میتوانید جهت دریافت مشخصات کامل هر محصول بر روی مدل آن کلیک نمایید مستقیما مشخصات کامل محصول مورد نظر شما نمایش داده خواهد شد.

دفتر مرکزی: 44184852 - 44186518 - 44185078
<http://naikel.ir> <http://telegram.me/naikelcctv>